

Package ‘SCVA’

July 25, 2019

Type Package

Title Single-Case Visual Analysis

Version 1.3.0

Date 2019-07-01

Author Isis Bulte and Patrick Onghena

Maintainer Tamal Kumar De <tamalkumar.de@kuleuven.be>

Description Make graphical representations of single case data and transform graphical displays back to raw data, as discussed in Bulte and Onghena (2013) <doi:10.22237/jmasm/1383280020>. The package also includes tools for visually analyzing single-case data, by displaying central location, variability and trend.

License GPL (>= 2)

Imports ggExtra, ggplot2, graphics, plotly, scales, stats, utils

Repository CRAN

NeedsCompilation no

Date/Publication 2019-07-25 08:10:11 UTC

R topics documented:

SCVA-package	1
AB	2
graph	3
graph.CL	4
graph.extract	6
graph.TREND	7
graph.VAR	9
graphly	11

SCVA-package

Single-Case Visual Analysis

Description

Make graphical representations of single case data and transform graphical displays back to raw data. The package also includes tools for visually analyzing single-case data, by displaying central location, variability and trend.

Details

Package: SCVA
Type: Package
Version: 1.3.0
Date: 2019-07-01
License: GPL version 2 or newer

Author(s)

Isis Bulte and Patrick Onghena

Maintainer: Tamal Kumar De <tamalkumar.de@kuleuven.be>

AB

Hypothetical AB data

Description

Hypothetical data collected in an AB phase design with 27 measurement times.

Usage

data(AB)

Format

A data frame with 27 observations.

- The first column contains the condition/phase labels ("A" and "B").
- The second column contains the obtained scores.
- The rows and columns are not labeled.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

Examples

```
data (AB)
```

```
graph
```

Graphical representation of single-case data

Description

The observed single-case data are plotted.

Usage

```
graph(design,data=read.table(file.choose(new=FALSE)),xlab="Measurement Times",
ylab="Scores",ylim=NULL,legendxy=NULL,labels=c("A","B","A","B"))
```

Arguments

design	Type of single-case design: "AB", "ABA", "ABAB", "CRD"(completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
data	File in which the data can be found. Default: a window pops up in which the file can be selected.
xlab	Label x axis.
ylab	Label y axis.
ylim	Y axis limits in the form <code>c(min,max)</code> .
legendxy	Optional legend location x and y coordinates in the form <code>c(x coordinate,y coordinate)</code> . Only used when design is "CRD", "RBD", "ATD" or "Custom".
labels	Optional labels for treatment levels in the form <code>c("A","B")</code> .

Details

When using the default `data` argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores. For multiple-baseline designs it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as NA. For calculations, missing data are omitted.

For alternation designs, after the plot is drawn, the location of the legend should be indicated by a left mouse click.

References

Bulte, I., & Onghena, P. (2008). An R package for single-case randomization tests. *Behavior Research Methods*, 40, 467-478.

Bulte, I., & Onghena, P. (2009). Randomization tests for multiple baseline designs: An extension of the SCRT-R package. *Behavior Research Methods*, 41, 477-485.

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

See Also

graph.CL to plot a measure of central tendency as a line parallel to the abscissa.

graph.VAR to display variability information.

graph.TREND to display a possible trend in the data.

graphly to display an interactive plot.

Examples

```
data(AB)
graph(design = "AB", data = AB)
```

graph.CL

Plot a measure of central tendency

Description

A measure of central tendency ((trimmed) mean, (broadened) median, M-estimator) is plotted as a horizontal reference line superimposed on the raw time series data.

Usage

```
graph.CL(design,CL,tr,data=read.table(file.choose(new=FALSE)),xlab="Measurement Time",
ylab="Scores",ylim=NULL,legendxy=NULL,labels=c("A","B","A","B"))
```

Arguments

design	Type of single-case design: "AB", "ABA", "ABAB", "CRD" (completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
CL	Measure of central tendency: "mean", "median", "bmed" (broadened median), "trimmean" (trimmed mean), or "mest" (M-estimator of location).

tr	If CL="trimmean": the percentage of observations that has to be removed from the end of the distribution before computing the mean. It can be any value from 0 (regular arithmetic mean) to 0.5. Usually 20 percent of the observations is trimmed (so tr=0.2). If CL="mest": the desired value for the constant K. Usually a percentile of the standard normal distribution is chosen. Wilcox (2005) suggests using K=1.28, which corresponds to the 90th percentile of the standard normal distribution and covers 80 percent of the underlying distribution.
data	File in which the data can be found. Default: a window pops up in which the file can be selected.
xlab	Label x axis.
ylab	Label y axis.
ylim	Y axis limits in the form c(min, max).
legendxy	Optional legend location x and y coordinates in the form c(x coordinate, y coordinate). Only used when design is "CRD", "RBD", "ATD" or "Custom".
labels	Optional labels for treatment levels in the form c("A", "B").

Details

When using the default data argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores. For multiple-baseline designs it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as NA. For calculations, missing data are omitted. Please note that some of the complicated plots may not work if there is missing data.

For alternation designs, after the plot is drawn, the location of the legend should be indicated by a left mouse click.

Note

For the calculation of the M-estimator of location, the function mest(x,bend=1.28) from Wilcox (2005) is used.

Wilcox, R.R. (2005). Introduction to robust estimation and hypothesis testing (2nd ed.). San Diego, CA: Elsevier Academic Press.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

See Also

graph to simply plot raw single-case data.

graph.VAR to display variability information.

graph.TREND to display a possible trend in the data.

graphly to display an interactive plot.

Examples

```
data(AB)
graph.CL(design = "AB", CL = "mean", data = AB)
```

graph.extract	<i>Extract raw data from graphs</i>
---------------	-------------------------------------

Description

Extract data values from existing graphs in jpeg format.

Usage

```
graph.extract(MT, refX, refY, save = "no", image = read.jpeg(file.choose()))
```

Arguments

MT	Measurement times: number of observations
refX	2 reference values for the X scale (e.g., refX=c(2, 14)).
refY	2 reference values for the Y scale (e.g., refY=c(10, 16)).
save	Save the extracted data points to a file (save="yes") or just see them as output in the R console (default: save="no").
image	Jpeg file in which the graph can be found. Default: a window pops up in which the file can be selected.

Details

When using the default image argument, a window will pop up to ask in what jpeg file the graph can be found.

Then the reference values should be located on the graph by clicking with the left mouse button: first the X values and then the Y values. The marked reference points are indicated with a blue cross.

Then each data point should be located sequentially. The marked data points are indicated with a red circle.

When finished, the calibrated true data points are displayed as output in the R console and plotted in a new graph, as a quick visual check.

When choosing to save these data values to a file (save="yes"), another window will pop up to ask where to save them. Here one can create a new txt file in the folder of choice.

Note

This function is an adaptation of: Timothee. (2010, March 5). Data visualization (in R). Getting data from an image (introductory post). [Web log message]. Retrieved from <http://rdataviz.wordpress.com/2010/03/05/getting-data-from-an-image-introductory-post/>.

We would like to thank David Howell for pointing us to this function.

The function based on functions adopted from the ReadImages package, which has been orphaned and archived by CRAN.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

graph.TREND

Plot a trend in central location

Description

Visualizes systematic shifts in central location over time using several methods. A vertical line graph plots the deviations from each data point to a measure of central tendency against time. Regression lines superimpose a linear function on the raw data by means of least squares regression, the split-middle method or the resistant trend line fitting method. The presence of a nonlinear trend can be displayed with running medians.

Usage

```
graph.TREND(design, TREND, CL, tr, data = read.table(file.choose(new = FALSE)),
            xlab = NULL, ylab = NULL, ylim = NULL, legendxy = NULL, labels = c("A", "B", "A", "B", "A", "B"))
```

Arguments

design	Type of single-case design: "AB", "ABA", "ABAB", "CRD"(completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
TREND	Trend visualization: vertical line plot ("VLP"); trend lines by means of least squares regression ("LSR"), split-middle method ("SM"), resistant trend line fitting ("RTL"), or running medians ("RM3", "RM5" or "RM42", depending on the desired batch size).
CL	Measure of central tendency: "mean", "median", "bmed" (broadened median), "trimmean" (trimmed mean), or "mest" (M-estimator of location).

tr	If CL="trimmean": the percentage of observations that has to be removed from the end of the distribution before computing the mean. It can be any value from 0 (regular arithmetic mean) to 0.5. Usually 20 percent of the observations is trimmed (so tr=0.2). If CL="mest": the desired value for the constant K. Usually a percentile of the standard normal distribution is chosen. Wilcox (2005) suggests using K=1.28, which corresponds to the 90th percentile of the standard normal distribution and covers 80 percent of the underlying distribution.
data	File in which the data can be found. Default: a window pops up in which the file can be selected.
xlab	Label x axis.
ylab	Label y axis.
ylim	Y axis limits in the form c(min, max).
legendxy	Optional legend location x and y coordinates in the form c(x coordinate, y coordinate). Only used when design is "CRD", "RBD", "ATD" or "Custom".
labels	Optional labels for treatment levels in the form c("A", "B").

Details

When using the default data argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores. For multiple-baseline designs it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as NA. For calculations, missing data are omitted. Please note that some of the complicated plots may not work if there is missing data.

For alternation designs, after the plot is drawn, the location of the legend should be indicated by a left mouse click.

Note

For the calculation of the M-estimator of location, the function mest(x,bend=1.28) from Wilcox (2005) is used.

Wilcox, R.R. (2005). Introduction to robust estimation and hypothesis testing (2nd ed.). San Diego, CA: Elsevier Academic Press.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

See Also

graph to simply plot raw single-case data.

graph.CL to plot a measure of central tendency as a line parallel to the abscissa.

graph.VAR to display variability information.

graphly to display an interactive plot.

Examples

```
data(AB)
graph.TREND(design = "AB", TREND = "VLP", CL = "mean", data = AB)
graph.TREND(design = "AB", TREND = "LSR", data = AB)
graph.TREND(design = "AB", TREND = "SM", data = AB)
graph.TREND(design = "AB", TREND = "RTL", data = AB)
graph.TREND(design = "AB", TREND = "RM3", data = AB)
graph.TREND(design = "AB", TREND = "RM5", data = AB)
graph.TREND(design = "AB", TREND = "RM42", data = AB)
```

graph.VAR

Plot an estimate of variability

Description

Information about variability in the data is displayed by three methods. Range bar graphs consist of a vertical line for each phase, created by connecting three points: an estimate of central tendency ((trimmed) mean, (broadened) median, M-estimator), the minimum and the maximum. Range lines consist of a pair of lines parallel to the X-axis, passing through the lowest and highest values for each phase, and superimposed on the raw data. Trended ranges display changes in variability within phases. For all these methods, the influence of outliers may be lessened by using a trimmed range, in which only a sample of the data set is used.

Usage

```
graph.VAR(design, VAR, dataset = "regular", CL, tr,
data = read.table(file.choose(new = FALSE)), xlab = NULL, ylab = NULL,
ylim = NULL, legendxy = NULL, labels = c("A", "B", "A", "B"))
```

Arguments

design	Type of single-case design: "AB", "ABA", "ABAB", "CRD"(completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
VAR	Estimate of variability: range bar graph ("RB"), range lines ("RL"), or trended range ("TR").
dataset	Use the whole dataset ("regular") or reduce the influence of outliers by removing the 10-20 percent extreme values from each phase ("trimmed"). Default: the whole dataset is used.
CL	Measure of central tendency: "mean", "median", "bmed" (broadened median), "trimmean" (trimmed mean), or "mest" (M-estimator of location).

<code>tr</code>	If <code>CL="trimmean"</code> : the percentage of observations that has to be removed from the end of the distribution before computing the mean. It can be any value from 0 (regular arithmetic mean) to 0.5. Usually 20 percent of the observations is trimmed (so <code>tr=0.2</code>). If <code>CL="mest"</code> : the desired value for the constant <code>K</code> . Usually a percentile of the standard normal distribution is chosen. Wilcox (2005) suggests using <code>K=1.28</code> , which corresponds to the 90th percentile of the standard normal distribution and covers 80 percent of the underlying distribution.
<code>data</code>	File in which the data can be found. Default: a window pops up in which the file can be selected.
<code>xlab</code>	Label x axis.
<code>ylab</code>	Label y axis.
<code>ylim</code>	Y axis limits in the form <code>c(min, max)</code> .
<code>legendxy</code>	Optional legend location x and y coordinates in the form <code>c(x coordinate, y coordinate)</code> . Only used when design is "CRD", "RBD", "ATD" or "Custom".
<code>labels</code>	Optional labels for treatment levels in the form <code>c("A", "B")</code> .

Details

When using the default `data` argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores. For multiple-baseline designs it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as `NA`. For calculations, missing data are omitted. Please note that some of the complicated plots may not work if there is missing data.

For alternation designs, after the plot is drawn, the location of the legend should be indicated by a left mouse click.

Note

For the calculation of the M-estimator of location, the function `mest(x,bend=1.28)` from Wilcox (2005) is used.

Wilcox, R.R. (2005). Introduction to robust estimation and hypothesis testing (2nd ed.). San Diego, CA: Elsevier Academic Press.

References

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

See Also

`graph` to simply plot raw single-case data.

`graph.CL` to plot a measure of central tendency as a line parallel to the abscissa.

`graph.TREND` to display a possible trend in the data.

`graphly` to display an interactive plot.

Examples

```
data(AB)
graph.VAR(design = "AB", VAR = "RB", CL = "mean", data = AB)
graph.VAR(design = "AB", VAR = "RL", data = AB)
graph.VAR(design = "AB", VAR = "TR", data = AB)
graph.VAR(design = "AB", VAR = "RL", dataset = "trimmed", data = AB)
```

graphly

Interactive plot of single-case data

Description

The observed single-case data are plotted using `plotly`, a web-based interactive charting library.

Usage

```
graphly(design, data=read.table(file.choose(new=FALSE)), xlab="Measurement Times",
        ylab="Scores", ylim=NULL, labels=c("A", "B", "A", "B"))
```

Arguments

<code>design</code>	Type of single-case design: "AB", "ABA", "ABAB", "CRD" (completely randomized design), "RBD" (randomized block design), "ATD" (alternating treatments design), "MBD" (multiple-baseline AB design) or "Custom" (user specified design).
<code>data</code>	File in which the data can be found. Default: a window pops up in which the file can be selected.
<code>xlab</code>	Label x axis.
<code>ylab</code>	Label y axis.
<code>ylim</code>	Y axis limits in the form <code>c(min, max)</code> .
<code>labels</code>	Optional labels for treatment levels in the form <code>c("A", "B")</code> .

Details

When using the default `data` argument, a window will pop up to ask in what file the data can be found. This text file containing the data should consist of two columns for single-case phase and alternation designs: the first with the condition labels and the second with the obtained scores. For multiple-baseline designs it should consist of these two columns for EACH unit. This way, each row represents one measurement occasion. It is important not to label the rows or columns.

Missing data should be indicated as `NA`. For calculations, missing data are omitted.

References

Bulte, I., & Onghena, P. (2008). An R package for single-case randomization tests. *Behavior Research Methods*, 40, 467-478.

Bulte, I., & Onghena, P. (2009). Randomization tests for multiple baseline designs: An extension of the SCRT-R package. *Behavior Research Methods*, 41, 477-485.

Bulte, I., & Onghena, P. (2012). When the truth hits you between the eyes: A software tool for the visual analysis of single-case experimental data. *Methodology*, 8, 104-114.

<http://ppw.kuleuven.be/home/english/research/mesrg>

<https://plotly-r.com/overview.html>

See Also

`graph` to simply plot raw single-case data.

`graph.CL` to plot a measure of central tendency as a line parallel to the abscissa.

`graph.VAR` to display variability information.

`graph.TREND` to display a possible trend in the data.

Examples

```
data(AB)
graphly(design = "AB", data = AB)
```

What's the right package manager to manage your dependencies? This article compares the pros and cons of each package manager and how to use them. With the advent of Swift 3.0, Apple has released an official package manager called Swift Package Manager (AKA SPM or SwiftPM), that helps us manage dependencies. But there are two other package managers out there: CocoaPods and Carthage. skip to package search or skip to sign in. Nourishing Pizza Microservice. Products. Build your NW.js app and generate archives, packages, setup files and more! nwjs-packager focuses on making building NW.js "just work". Key Features. Moves your app's files to a temporary directory and runs `npm install --production`. This package contains AI flight plans and nine SCVA AI aircraft, including B727-200 and B737-800 models by AI Aardvark, B757-200 and CRJ900 models by Alpha India Group and Dash 8-400 model by The Fruit Stand. The flight plans are in an easy to install traffic file and cover the SCVA route network Type. Complete with Base Model.